Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (currently amended) Apparatus for filtering and entrapping debris from the <u>a</u> vascular system of a patient, said apparatus comprising:

a filter device being sized to allow blood flow therethrough and to restrict passage of debris therethrough, and said filter device having a first given perimeter, a proximal side and a distal side; and

wherein said filtering device captures debris carried in a first direction of blood flow from said proximal side to said distal side thereof on said proximal side of said filter device;

an entrapment <u>device mechanism</u> having a proximal side and a distal side, said entrapment <u>device mechanism</u> including a <u>at least one</u> selective opening <u>of a size</u> to allow passage of debris and blood therethrough, said selective opening <u>being configured to allow allowing</u> passage of blood and debris carried therein therethrough in said first direction of blood flow from said proximal side to said distal side of said entrapment <u>mechanism device and from said entrapment</u> <u>device to said filtering device</u>, said selective opening having a restriction <u>element mechanism</u> <u>operatively provided</u> to prevent debris passage <u>back through said selective opening</u> from said distal side to said proximal side of said entrapment <u>device mechanism</u> in a second direction opposite to said first direction, said selective opening forming a second given perimeter, and said first given perimeter and said second given perimeter being <u>deployable deployed</u> within the vascular system so as to form a chamber between said distal side of said entrapment <u>device</u> <u>mechanism</u> and said proximal side of said filtering device <u>with respect to blood flow through</u> <u>both of said entrapment device and said filtering device</u>;

wherein said entrapment mechanism allows blood and debris carried therein therethrough in said first direction of blood flow, said filtering device allows blood therethrough in said first direction of blood flow, and said restriction element mechanism prevents debris back through said selective opening in said second direction of blood flow opposite to said first direction of blood flow such that said chamber entraps the filtered debris received therein for debris removal from the vascular system of the patient.

- 2. (original) Apparatus according to claim 1 further comprising an introduction mechanism including a cannula to insert said filter device and said entrapment mechanism into the vascular system of the patient.
- 3. (currently amended) Apparatus according to claim 1 further comprising a deployable frame being selectively configurable to adjustably size said filter device and entrapment device mechanism between a first position and a second position.
- 4. (original) Apparatus according to claim 3 further comprising a compliant outer cuff being configured to surround said deployable frame, and to make contact with an inner wall of the vascular system of the patient.
- 5. (original) Apparatus according to claim 4 wherein said compliant outer cuff passively surrounds said deployable frame.
- 6. (original) Apparatus according to claim 4 wherein said compliant outer cuff is radially expandable.

Serial No. 10/772,782

Page 4

- 7. (original) Apparatus according to claim 1 wherein said filter device comprises a filter bag.
- 8. (currently amended) Apparatus according to claim 1 wherein said entrapment <u>device</u> mechanism comprises at least one entrapment leaflet attached to a first portion on said distal side of said entrapment <u>device</u> mechanism and contacting a <u>distal surface</u> second portion on said distal side of said entrapment <u>device</u> mechanism such that said at least one entrapment leaflet <u>can</u> be is positioned away from said second distal surface of said entrapment <u>device</u> mechanism to allow blood and debris in said first direction of blood flow therethrough and said at least one entrapment leaflet <u>can</u> be is positioned toward said second distal surface of said entrapment <u>device</u> mechanism to prevent debris in said second direction of blood flow therethrough.
- 9. (currently amended) Apparatus according to claim 8 wherein said at least one entrapment leaflet comprises a filter material so as to allow blood, and to prevent debris, in said second direction of blood flow back through said entrapment device mechanism.
- 10. (currently amended) Apparatus according to claim 8 wherein said at least one entrapment leaflet comprises a non-porous material so as to prevent blood and debris in said second direction of blood flow back through said entrapment device mechanism.
- 11. (currently amended) Apparatus according to claim 8 further comprising a perimeter seal extending about the interior of said entrapment <u>device</u> mechanism so as to provide selectable engagement with said at least one entrapment leaflet in said second direction of blood flow.

Serial No. 10/772,782 Page 5

- 12. (currently amended) Apparatus according to claim 8 wherein said <u>distal surface</u> second portion of said entrapment <u>device</u> mechanism is <u>provided by</u> a piece of coarse mesh extending across the interior of said entrapment <u>device</u> mechanism so as to provide selectable engagement with said at least one entrapment leaflet in said second direction of blood flow.
- 13. (currently amended) Apparatus according to claim 8 wherein said <u>distal surface</u> second portion of said entrapment <u>device</u> mechanism is <u>provided by</u> at least one co-aptation strand extending across the interior of said entrapment <u>device</u> mechanism so as to provide selectable engagement with said at least one entrapment leaflet in said second direction of blood flow.
- 14. (original) Apparatus according to claim 1 wherein said first direction of blood flow is the direction of systolic blood flow and said second direction of blood flow is the direction of diastolic blood flow.
- 15. (original) Apparatus according to claim 1 wherein said first direction of blood flow is the direction of diastolic blood flow and said second direction of blood flow is the direction of systolic blood flow.
- 16. (canceled)
- 17. (canceled)
- 19. (canceled)

Serial No. 10/772,782 Page 6

20. (canceled)